





The green green grass of home.

With its 35 mm pile height and high stitch density, Iska eco provides a luxurious look and feel that transforms any space into a dream setting. But there's more to Iska than meets the eye: it not only is extremely strong and durable, it also features our proprietary eco-backing.

STANDARD ROLLS

Pile out

2×20 m - 4×20 m

WARRANTY (Years - KLy)

8 - 1000 KLy*

TESTS AND CERTIFICATES

DURABILITY_

- ISO 9001_QUALITY MANAGEMENT
- Colour fastness ≥ 4
- Water permeability 60l/min/m²

ENVIRONMENT_

• ISO 14001_ENVIRONMENTAL MANAGEMENT

SAFETY_

- Fire certification: Efl
- ISO 45001_Occupational health and safety management systems
- Social Audit, 2-Pillar SMET

Technical characteristics

Yarn



Type: Monofilament + Texturized

 Composition:
 60% PE - 40% PP

 Dtex.:
 7400 DTex (±5%)

 Pile weight:
 1810 gr/m² (±10%)

 Colors:
 Monofilament: Dragon

Texturized: Cream / Green / Brown

Tufting

Gauge: 3/8"

Pile height: 35 mm (±5%)

Total height: 37 mm (±5%)

Stitches: 295 lm (±10%) - 30975 m² (±10%)

Backing construction

Primary backing: Single Backing

100% pp, uv Stabilized

Finishing: Verdite Monobacking

DAG.410.MAR.15 / 2 / 1-9-24

REMARKS

In case infill is added to the Turfgrass artificial grass, please use rounded (non-angular), sieved, washed and dried silica sand. The use of any other type of infill material will invalidate the Turfgrass warranty.

*The standard warranties are applicable for regions with Global horizontal irradiation lower than or equal to 1800 KWH/m2/year or 155 KLy/m2/year. For regions with Global Horizontal Irradiation more than 1800 KWH/m2/year or 155 KLy/m2/year, please refer to our warranty statement.



Final product

Total weight: 2360 gr/m² (±10%)





In order to constantly improve the quality of our products to the latest technical standards, Turfgrass® reserves the right to modify any of the technical characteristics. The stated values are approximate average values and may vary by $\pm 10\%$ (fibre height $\pm 5\%$) due to technical reasons.



